


# CARBIDE FULL ROD

## Common Size Full Rods



Ground to h6 Tolerance..  
Standard Rod

ISO CODE K20-K40  
Grain Size Submicron  
Cobalt Content Wt% 10  
Density g/cm<sup>3</sup> 14.38  
HV30 1600  
HRA 91.9  
TRS(ISO3327)N/mm<sup>2</sup> 4000  
KICMpa\*m<sup>1/2</sup> 10.4

Part No	D1	L1
	Diameter h6	Overall Length
ESCR2x330	2.0	330mm
ESCR3x330	3.0	330mm
ESCR4x330	4.0	330mm
ESCR5x330	5.0	330mm
ESCR6x330	6.0	330mm
ESCR7x330	7.0	330mm
ESCR8x330	8.0	330mm
ESCR9x330	9.0	330mm
ESCR10x330	10.0	330mm
ESCR12x330	12.0	330mm
ESCR14x330	14.0	330mm
ESCR15x330	15.0	330mm
ESCR16x330	16.0	330mm
ESCR18x330	18.0	330mm
ESCR20x330	20.0	330mm
ESCR22x330	22.0	330mm
ESCR24x330	24.0	330mm
ESCR25x330	25.0	330mm
ESCR28x330	28.0	330mm
ESCR30x330	30.0	330mm
ESCR32x330	32.0	330mm
ESCR40x330	40.0	330mm
ESCR18x330	1/8"	330mm
ESCR316x330	3/16"	330mm
ESCR14x330	1/4"	330mm
ESCR516x330	5/16"	330mm
ESCR38x330	3/8"	330mm
ESCR12x330	1/2"	330mm
ESCR34x330	3/4"	330mm
ESCR1x330	1"	330mm